

TACTYLE CR™

www.cordovasafety.com

SHELL CONSTRUCTION

- TACTYLE CR™, 18-Gauge
- HPPE/Steel Shell
- Reinforced Thumb Crotch
- Touchscreen Fingertips

COATING

- TUF-COR™ Nitrile Coating

PERFORMANCE INFORMATION

- ANSI/ISEA 105-2016
- Cut Level A6
- Abrasion Level 6
- Puncture Level 4



DESCRIPTION:

TACTYLE™ CR: 18-Gauge, HPPE/Steel Shell, TUF-COR™ Nitrile Coating, ANSI/ISEA 105-2016 Cut Level A6: 6685

TACTYLE™ CR: 18-Gauge, HPPE/Steel Shell, TUF-COR™ Nitrile Coating, Reinforced Thumb Crotch, Touchscreen, ANSI/ISEA 105-2016 Cut Level A6

CERTIFICATIONS & RATINGS:

Component Materials comply with all federal regulations for food contact. (U.S. Code of Federal Regulations, 21CFR, Parts 170-199)

APPLICATIONS:



GLASS HANDLING



RECYCLING OPERATIONS



PLASTIC EXTRUSION



METAL FABRICATION

ORDERING:

Unit of Sale: One Pair
Packaging: 12 Prs/Polybag
Case Pack: 144 Pairs
COO: China
Available Sizes: S-2XL

Case Weight (lbs)	S	M	L	XL	XXL
	16.50	19.40	19.60	21.60	22.90

BARCODES:

ITEM	DOZEN	CASE
6685S	796326040157	50796326040152
6685M	796326040164	50796326040169
6685L	796326040171	50796326040176
6685XL	796326040188	50796326040183
6685XXL	796326040195	50796326040183

CARE:

Wash using warm water and commercial laundry detergent. Water temperature not to exceed 50°C/122°F. Air-dry or tumble-dry with low heat.

Corporate Headquarters:

4025 Viscount Avenue
 Memphis, TN 38118
 Phone 800.458.8763
 Fax 901.458.3343

CORE SAFETY PROTECTION
www.cordovasafety.com

West Coast Office:

433 Cheryl Lane (Dock Door 14)
 City of Industry, CA 91789
 Phone 909.590.2679
 Fax 909.590.3130