

H500 HARNESS

TECHNICAL DATA
SP560 Rev. A
Jul. 2024

The Honeywell Miller H500 integrates anatomically and ergonomically designed breathable paddings, offers more freedom of movement, and introduces a variety of other new features, including a new smart anti-tangle solution for a hassle-free donning experience.

MATERIALS

Webbing:	Stretchable Polyester (Neon Green or Black)
Elastic Keepers:	Elastic
Thread:	Polyester
Grommets:	Stainless Steel
Hardware:	Zinc Plated Steel or aluminum with clear chromate
Back,Shoulder Pads:	Nylon
Pad Mesh Shield:	EVA Foam
Label Pack:	Polyethylene, Polyester

TECHNICAL

Max.Working Load:	420 lb (190.5kg)
Webbing Min. Tensile:	5,000 lb (22 kN)
D-Ring Min. Tensile:	5,000 lb (22 kN)

CERTIFICATION


Harness meets OSHA 1926.502
Certified ANSI Z359.11-2021 and *CSA Z259.10-2018
* Harnesses meet variations of CSA classes A, E, L and P. See labels for details



Variant	SKU	Size	Weight	Legs Buckles	Chest Buckles	D-Rings				Small Shoulder Pads	SRL Web Link	CSA Class
						Back	Front	Side	Shldr.			
CC1	H5CC311021	S/M	5.2 lb (2.3 kg)	Tongue	Mating	Steel	0	Steel	0	0	1	A,P
	H5CC311022	UNIV	5.4 lb (2.4 kg)									
	H5CC311023	XXL	5.5 lb (2.5 kg)									
CC2	H5CC311121	S/M	5.4 lb (2.4 kg)	Tongue	Mating	Steel	Steel	Steel	0	0	1	A, L, P
	H5CC311122	UNIV	5.7 lb (2.5 kg)									
	H5CC311123	XXL	5.8 lb (2.6 kg)									
CC3	H5CC312221	S/M	5.3 lb (2.4 kg)	Tongue	Mating	Alum	Alum	Alum	0	0	1	A, L, P
	H5CC312222	UNIV	5.6 lb (2.5 kg)									
	H5CC312223	XXL	5.6 lb (2.5 kg)									
CC4	H5CC222221	S/M	5.5 lb (2.5 kg)	Quick Conn.	Quick Conn.	Alum	Alum	Alum	0	0	1	A, L, P
	H5CC222222	UNIV	5.7 lb (2.6 kg)									
	H5CC222223	XXL	5.8 lb (2.6 kg)									
CC5	H5CC222021	S/M	5.3 lb (2.4 kg)	Quick Conn.	Quick Conn.	Alum	0	Alum	0	0	1	A,P
	H5CC222022	UNIV	5.8 lb (2.5 kg)									
	H5CC222023	XXL	5.6 lb (2.5 kg)									
CC6	H5CC221121	S/M	5.8 lb (2.6 kg)	Quick Conn.	Quick Conn.	Steel	Steel	Steel	0	0	1	A, L, P
	H5CC221122	UNIV	6.0 lb (2.7 kg)									
	H5CC221123	XXL	6.1 lb (2.7 kg)									
CC7	H5CC311001	S/M	4.9 lb (2.2 kg)	Tongue	Mating	Steel	0	0	0	0	1	A
	H5CC311002	UNIV	5.1 lb (2.3 kg)									
	H5CC311003	XXL	5.2 lb (2.3 kg)									
CS1	H5CS311021	S/M	6.0 lb (2.7 kg)	Tongue	Mating	Steel	0	Steel	0	2	0	A,P
	H5CS311022	UNIV	6.2 lb (2.8 kg)									
	H5CS311023	XXL	6.3 lb (2.8 kg)									
CS1S	H5CS31102S1	S/M	6.2 lb (2.8 kg)	Tongue	Mating	Steel	0	Steel	2	2	0	A, E, P
	H5CS31102S2	UNIV	6.4 lb (2.9 kg)									
	H5CS31102S3	XXL	6.5 lb (2.9 kg)									
CS2	H5CS311121	S/M	6.2 lb (2.8 kg)	Tongue	Mating	Steel	Steel	Steel	0	2	0	A, L, P
	H5CS311122	UNIV	6.4 lb (2.9 kg)									
	H5CS311123	XXL	6.5 lb (2.9kg)									
CS3	H5CS221021	S/M	3.4 lb (1.5 kg)	Quick Conn.	Quick Conn.	Steel	0	Steel	0	2	0	A,P
	H5CS221022	UNIV	3.5 lb (1.6 kg)									
	H5CS221023	XXL	3.6 lb (1.6 kg)									
IC1	H5IC311001	S/M	3.6 lb (1.6 kg)	Tongue	Mating	Steel	0	0	0	0	1	A
	H5IC311002	UNIV	3.8 lb (1.7 kg)									
	H5IC311003	XXL	3.8 lb (1.7 kg)									
IC2	H5IC221001	S/M	3.6 lb (1.6 kg)	Quick Conn.	Quick Conn.	Steel	0	0	0	0	1	A
	H5IC221002	UNIV	3.8 lb (1.7 kg)									
	H5IC221003	XXL	3.8 lb (1.7 kg)									

Variant	SKU	Size	Weight	Legs Buckles	Chest Buckles	D-Rings				Small Shoulder Pads	SRL Web Link	CSA Class
						Back	Front	Side	Shldr.			
IC3	H5IC222021	S/M	4.1 lb (1.8 kg)	Quick Conn.	Quick Conn.	Alum	0	Alum	0	0	1	A,P
	H5IC222022	UNIV	4.2 lb (1.9 kg)									
	H5IC222023	XXL	4.3 lb (1.9 kg)									
IC4	H5IC221021	S/M	4.2 lb (1.9 kg)	Quick Conn.	Quick Conn.	Steel	0	Steel	0	0	1	A,P
	H5IC221022	UNIV	4.4 lb (2.0 kg)									
	H5IC221023	XXL	4.4 lb (2.0 kg)									
IC5	H5IC311121	S/M	4.2 lb (1.9 kg)	Tongue	Mating	Steel	Steel	Steel	0	0	1	A, L, P
	H5IC311122	UNIV	4.4 lb (2.0 kg)									
	H5IC311123	XXL	4.4 lb (2.0 kg)									
IC6	H5IC221101	S/M	3.6 lb (1.6 kg)	Tongue	Quick Conn.	Quick Conn.	Steel	Steel	0	0	0	1
	H5IC221102	UNIV	3.8 lb (1.7 kg)									
	H5IC221103	XXL	3.8 lb (1.7 kg)									
IS1P	H5ISP311001	S/M	3.3 lb (1.5 kg)	Tongue	Mating	Steel	0	0	0	2	0	A
	H5ISP311002	UNIV	3.5 lb (1.6kg)									
	H5ISP311003	XXL	3.6 lb (1.6 kg)									
IS2P	H5ISP311021	S/M	3.8 lb (1.7 kg)	Tongue	Mating	Steel	0	Steel	0	2	0	A,P
	H5ISP311022	UNIV	4.1 lb (1.8 kg)									
	H5ISP311023	XXL	4.1 lb (1.8 kg)									
IS3	H5IS311101	S/M	3.2 lb (1.4 kg)	Tongue	Mating	Steel	Steel	0	0	0	0	A
	H5IS311102	UNIV	3.4 lb (1.5 kg)									
	H5IS311103	XXL	3.5 lb (1.6 kg)									
IS3S	H5IS31110S1	S/M	3.7 lb (1.7 kg)	Tongue	Mating	Steel	Steel	0	2	0	0	A, E
	H5IS31110S2	UNIV	4.0 lb (1.8 kg)									
	H5IS31110S3	XXL	4.0 lb (1.8 kg)									
IS4	H5ISP311021	S/M	3.8 lb (1.7 kg)	Tongue	Mating	Steel	Steel	Steel	0	0	0	A, L, P
	H5ISP311022	UNIV	4.0 lb (1.8 kg)									
	H5ISP311023	XXL	4.1 lb (1.8 kg)									
IS5P	H5IS311101	S/M	3.4 lb (1.5 kg)	Quick Conn.	Quick Conn.	Steel	0	0	0	2	0	A
	H5IS311102	UNIV	3.6 lb (1.6 kg)									
	H5IS311103	XXL	3.7 lb (1.6 kg)									
IS6P	H5IS31110S1	S/M	2.9 lb (1.3 kg)	Mating	Mating	Steel	0	0	0	2	0	A
	H5IS31110S2	UNIV	3.1 lb (1.4 kg)									
	H5IS31110S3	XXL	3.2 lb (1.4 kg)									
IS7P	H5ISP321001	S/M	3.5 lb (1.6 kg)	Mating	Mating	Steel	0	Steel	0	2	0	A,P
	H5ISP321002	UNIV	3.7 lb (1.7 kg)									
	H5ISP321003	XXL	3.8 lb (1.7 kg)									
IS8P	H5ISP221021	S/M	3.4 lb (1.5 kg)	Tongue	Quick Conn.	Steel	0	0	0	2	0	A
	H5ISP221022	UNIV	3.6 lb (1.6 kg)									
	H5ISP221023	XXL	3.7 lb (1.6 kg)									

VARIANT	SKU	SIZE	WEIGHT	LEGS BUCKLES	CHEST BUCKLES	D-RINGS				SMALL SHOULDER PADS	SRL WEB LINK	CSA CLASS
						BACK	FRONT	SIDE	SHLDR.			
IS9P	H5ISP221021	S/M	4.0 lb (1.8 kg)	Quick Conn.	Quick Conn.	Steel	0	Steel	0	2	0	A,P
	H5ISP221022	UNIV	4.2 lb (1.9 kg)									
	H5ISP221023	XXL	4.3 lb (1.9 kg)									
IS10	H5IS321101	S/M	3.6 lb (1.6 kg)	Tongue	Quick Conn.	Steel	Steel	0	0	0	1	A
	H5IS321102	UNIV	3.9 lb (1.7 kg)									
	H5IS321103	XXL	3.9 lb (1.8 kg)									
IS11	H5IS321111	S/M	4.2 lb (1.9 kg)	Tongue	Quick Conn.	Steel	Steel	Steel	0	0	1	A, L, P
	H5IS321112	UNIV	4.5 lb (2.0 kg)									
	H5IS321113	XXL	4.5 lb (2.0 kg)									



Limitless Possibilities. Ask the Expert.
 Technical Service: 800.873.5242
www.millerfallprotection.com

Honeywell Safety Products USA, Inc.
 855 S Mint St
 Charlotte, NC 28202
www.honeywell.com

USA
 Phone: 800.430.5490
 Fax: 800.322.1330

⚠ This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.

Canada
 Phone: 888.212.7233
 Fax: 888.667.8477

Honeywell
MILLER