

G304 | G304T | G304TN



Top Shelf Chemical Splash Goggle

Part	Lens
G304 • • •	<input type="checkbox"/> Clear
G304T • • • •	<input type="checkbox"/> Clear H2X Anti-Fog
G304TN • • •	<input type="checkbox"/> Clear H2X Anti-Fog with Neoprene Strap

- Body tinted to reduce glare.
- Special one-way vent allows air to enter while keeping liquids out.
- Top shelf chemical splash goggle features generously sized heavy duty body and lens.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

GENERAL SPECIFICATION




Bridge: 42mm
Lens Base: 4.25 curve
Lens Size Diagonal: 150mm
Lens Size Vertical: 76mm
Lens Thickness: 2.2mm
Overall Length [Lens-Tip]: N/A
Overall Width [Hinge-Hinge]: 180mm
PD: 68mm
Weight: 68gm

PACKAGING

Polybag: 1pc
Inner Box: 12 pcs
Case: 144 pcs

G304 | G304T | G304TN

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Lens inset in PVC frame
Frame	PVC	Polyvinyl chloride, flexible fit
Nose Piece	PVC	Integral to frame
2 cap vents	LPDE	Also hold elastic band in place
Elastic Band	60% polyester 40% rubber thread	N/A

PART	LENS	LENS MARKING	FRAME MARKING
G304	 Clear	P	P Z87 + / P c SEI CAN/CSA Z94.3-07
G304T	 Clear H2X Anti-Fog	P	P Z87 + D3 D4 / P c SEI CAN/CSA Z94.3-07
G304TN	 Clear H2X Anti-Fog	P	P Z87 +

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

D3: Droplet & Splash Test

D4: Dust Test

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices