

Universal Sock/Net Boom #GB510SN - 5" x 10' 4/package



Fast, efficient response for large spills.

- Just one of these high-capacity booms can contain and soak up 5.8 gallons of oils, coolants, solvents or water
- Booms won't shed, even when saturated
- A nylon rope and sturdy hardware ensure long-lasting durability and easy retrieval
- Use boom connectors to create a containment system big enough to handle almost any size spill
- UPS does not allow this item to ship in bag pkg'ing. Therefore, we must BOX any UPS orders at an additional cost of \$4.50/per box. This is ONLY for UPS shipments. This does not affect LTL/palletized shipments of this item.

GB510SN Specifications

Dimensions:	ext. dia. 5" x 10' L
Shipping Dimensions:	20" W x 23" L x 20" H
Sold as:	4 booms per package
Color:	Gray
Composition:	Poly Blend
Absorbency:	Up to 23.3 gal. per package
Absorbency per:	Up to 5.8 gal. per boom
Weight:	23 lbs.
# per Pallet:	20
Incinerable:	Yes
Ship Class:	175

Metric Equivalent Specifications

Dimensions:	ext. dia. 13cm x 3m L
Shipping Dimensions:	51cm W x 58cm L x 51cm H
Absorbency:	Up to 88.2 L per package
Absorbency per:	Up to 22 L per boom
Weight:	10.4 kg



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com

GB510SN Technical Information

Warnings & Restrictions:

Color Variance Notice
Color may vary.

Regulations and Compliance:

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 122.26 - Facilities must have a detailed plan in place to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com