

Goliath® ANSI • CE • CSA •



CO-INJECTED
TEMPLES



POLARIZED
OPTIONS

Co-injected rubber
temples // Custom
imprinting available



Black Frame | 9 Variations

SB5610D • • •	Clear
SB5610DT •	Clear H2X AF
SB5620D • • •	Gray
SB5620DT • • •	Gray H2X AF
SB5621D • • •	Polarized Gray
SB5645D • • •	Ice Orange Mirror
SB5665D • • •	Ice Blue Mirror
SB5670D • •	Silver Mirror
SB5680D •	I/O Mirror

White Frame | 2 Variations

SW5655D • •	Sky Red Mirror
SW5665D • • •	Ice Blue Mirror



SW56

Part No.	Lens Markings	Frame Markings	General Specifications	Materials
SB5610D	P + U6	P Z87 + / P c SEI Z94.3	Weight: 35 gm	Lens: polycarbonate
SB5610DT	P + U6	P Z87 +	PD: 68 mm	Temples: polycarbonate & thermoplastic rubbers
SB5620D	P + U6 L2.5	P Z87 + / P c SEI Z94.3	Bridge: 13.8 mm	Hinge: polycarbonate
SB5620DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3	Lens base: 8 curve	Screw: stainless steel
SB5621D	P + S	P Z87 + / P c SEI Z94.3	Lens size diagonal: 62.6 mm	Side shields: polycarbonate
SB5645D	P + S	P Z87 + / P c SEI Z94.3	Lens size vertical: 37.6 mm	
SB5645D	P + S	P Z87 + / P c SEI Z94.3	Lens thickness: 2.3 mm	
SB5665D	P + S	P Z87 + / P c SEI Z94.3	Overall length (lens - tip): 163.5 mm	
SB5670D	P + S	P Z87 + / P c SEI Z94.3	Overall width (hinge - hinge): 131 mm	
SB5680D	P + U6 L1.7	P Z87 +	Closest point between lens: 18 mm	
SW5655D	P + S	P Z87 + / P c SEI Z94.3		
SW5665D	P + S	P Z87 + / P c SEI Z94.3		

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

S: Special Purpose

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices