



RUBBER
TIPS



RUBBER
NOSE PIECE



READER



CUSTOM
LOGO

EMERGE[®] PLUS

ANSI/ISEA • CE/UKCA • CAN/CSA •

Rubber temple tips // Soft nosepiece provides comfort
for extended use // Custom imprinting available

Full Readers

Translucent Gray Frame | 7 Variations

SG9810R15 • • •	Clear	+1.5 Mag
SG9810R20 • • •	Clear	+2.0 Mag
SG9810R25 • • •	Clear	+2.5 Mag
SG9810R30 • • •	Clear	+3.0 Mag
SG9820R15 •	Gray	+1.5 Mag
SG9820R20 •	Gray	+2.0 Mag
SG9820R25 •	Gray	+2.5 Mag



Materials

Lens: Polycarbonate
Frame: Nylon
Nosepiece: Thermosplastic Rubbers (TPR)
Hinge: Polycarbonate
Temples: Polycarbonate
Temple Tips: Thermosplastic Rubbers (TPR)
Screw: Stainless Steel

Part No.	Lens Marking	Temple Marking	Lens Marking Symbols	Temple Marking Symbols	Measurements
SG9810R15	P Z87 + U6	+1.50 P Z87 - 2 + / P c SEI Z94.3	P: Manufacturer's mark	+1.50: magnification of +1.5	Weight: 31.3 gm
SG9810R20	P Z87 + U6	+2.00 P Z87 - 2 + / P c SEI Z94.3	Z87: ANSI standard for eye and face protection devices	+2.00: magnification of +2.0	Bridge: 10.6 mm
SG9810R25	P Z87 + U6	+2.50 P Z87 - 2 + / P c SEI Z94.3	+: High impact	+2.50: magnification of +2.5	Lens base: 6 curve
SG9810R30	P Z87 + U6	+3.00 P Z87 - 2 + / P c SEI Z94.3	UV Filter Transmittance	+3.00: magnification of +3.0	Lens size diagonal: 54.6 mm
SG9820R15	P Z87 + U6 L2.5	+1.50 P Z87 - 2 +	U6: .01% max effective far UV • .1% max near UV	P: Manufacturer's mark	Lens size vertical: 42.5 mm
SG9820R20	P Z87 + U6 L2.5	+2.00 P Z87 - 2 +	Visible Light Filters	Z87: ANSI standard for eye and face protection devices	Lens thickness: 2.2 mm
SG9820R25	P Z87 + U6 L2.5	+2.50 P Z87 - 2 +	L2.5: 29% max visible light	- 2: Rx	Overall length (lens - tip): 160 mm
				+: High impact	Overall width (hinge - hinge): 129 mm
				c SEI Z94.3: CAN/CSA standard for eye and face protection devices	